

Instructions included

Take your first test today

Installing the batteries

If this is your first time using the device:

- To remove the back cover compartment, push the white button and follow the direction of the printed arrows.
- 2 Install two AAA batteries into the battery compartment. Match the plus (+) and minus (-) signs in the compartment. If the polarities are not matched, damage to the oximeter may occur.
- 3 Slide the battery door cover horizontally in the direction of the arrow.



Taking a measurement

- 1 Press the Power/Function button.
- 2 Place one finger into the rubber hole of the oximeter (it is best to plug the finger thoroughly) before releasing the clamp, with the nail upward.
- 3 The data (SpO₂ and Pulse Rate) will appear on the device. Don't move the finger; be sure to remain motionless during the reading.
 - Once the measurement is finished, it will display "Thank you". Remove your finger. The device will turn off automatically.
- 5 Log into your portal to see your results today.

Distributed by:

Telcare, LLC 600 West Ridge Road Suite 200 Linwood, PA 19061

Phone:

(888) 666-4530 (US /EE.UU.)

(1) (978) 610-4688 (International)

Monday - Friday, 9AM - 9PM EST

Email:

VCM-customercare@philips.com

www.philips.com/virtualcaremanagement

The Terms of Service ("Terms") outline the terms regarding your use of our products and can be found at www.philips.com/virtualcaremanagement/terms. If you do not agree with these Terms, do not register or use any of the Services.

© 2023 Koninklijke Philips N.V. All rights reserved.